

30H / 30WH

3/4" (19mm) Full Circle, Brass Impact Sprinkler

- Heavy duty brass construction
- Stainless steel springs and fulcrum pin
- Chemically resistant washers

Features

- Dual nozzle ports
- 30H unit does not have a spreader plug
- 30WH unit has spreader plug

Benefits

- Wide range of flow rates
- Corrosion and grit resistant
- Built to last
- Five-year Customer Satisfaction Policy

Specifications

- Bearing: 3/4" (19mm) Male NPT, Brass
- Trajectory Angle: 27°
- Operating Range: 25-80 psi (1.7-5.5 bar)
- Flow Rate: 2.9-13.1 gpm (0.66-2.98 m3/h)
- Radius: 40-56 ft. (12.20-17.23 meters)
- Nozzle Port: 1/8" Female NPT
- Spreader Nozzle Port: 1/8" Female NPT



Brass Straight Bore Nozzle (SBN-3) with Plug Performance*

psi@ Nozzle	NOZZLE SIZE (Stream Height: 9 ft.)			
	9/64"	5/32"	11/64"	3/16"
	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)
25	40 2.90	41 3.50	41 4.30	42 5.10
30	40 3.10	42 3.90	44 4.70	45 5.60
35	41 3.40	43 4.20	45 5.10	47 6.00
40	41 3.60	44 4.50	46 5.40	48 6.40
45	42 3.80	44 4.70	46 5.70	49 6.80
50	42 4.10	45 5.00	47 6.10	50 7.20
55	43 4.20	45 5.20	48 6.30	50 7.60
60	43 4.40	46 5.50	48 6.60	51 7.90
65	44 4.60	46 5.80	49 6.90	51 8.20
70	44 4.80	47 5.90	49 7.20	52 8.50
75	45 5.00	47 6.10	50 7.40	52 8.80
80	45 5.10	48 6.30	50 7.70	53 9.10

Brass Straight Bore Nozzle (SBN-3) with Spreader (LAN-1) Performance*

psi@ Nozzle	NOZZLE SIZE (Stream Height: 9 ft.)				
	9/64" x 3/32-7"	5/32" x 3/32-7"	11/64" x 3/32-7"	3/16" x 3/32-7"	3/16" x 1/8-20"
	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)
25	40 4.20	41 4.80	41 5.60	42 6.40	42 7.40
30	40 4.60	42 5.30	44 6.10	45 7.00	45 8.10
35	41 4.90	43 5.70	45 6.60	47 7.50	47 8.70
40	41 5.20	44 6.10	46 7.00	48 8.10	48 9.30
45	42 5.60	44 6.50	46 7.40	49 8.50	49 9.90
50	42 5.90	45 6.80	47 7.90	50 9.00	50 10.40
55	43 6.10	45 7.10	48 8.20	50 9.40	50 10.90
60	43 6.40	46 7.40	48 8.60	51 9.90	51 11.40
65	44 6.70	46 7.80	49 8.90	51 10.20	51 11.80
70	44 6.90	47 8.10	49 9.30	52 10.70	52 12.30
75	45 7.20	47 8.30	50 9.60	52 11.00	52 12.70
80	45 7.50	48 8.70	50 10.00	53 11.50	53 13.10

Brass Straight Bore Nozzle with Vane (SBN-3V) with Plug Performance*

psi@ Nozzle	NOZZLE SIZE (Stream Height: 10 ft.)			
	9/64"	5/32"	11/64"	3/16"
	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)
25	42 2.90	44 3.50	45 4.30	48 5.10
30	43 3.10	45 3.90	46 4.70	47 5.60
35	44 3.40	46 4.20	47 5.10	49 6.00
40	45 3.60	47 4.50	48 5.40	50 6.40
45	46 3.80	48 4.70	49 5.70	52 6.80
50	46 4.10	49 5.00	50 6.10	53 7.20
55	47 4.20	50 5.20	51 6.30	53 7.60
60	47 4.40	50 5.50	51 6.60	54 7.90
65	48 4.60	51 5.80	52 6.90	55 8.20
70	48 4.80	51 5.90	53 7.20	55 8.50
75	49 5.00	52 6.10	54 7.40	56 8.80
80	50 5.10	52 6.30	55 7.70	56 9.10

Brass Straight Bore Nozzle with vane (SBN-3v) with Spreader (LAN-1) Performance*

psi@ Nozzle	NOZZLE SIZE (Stream Height: 10 ft.)				
	9/64" x 3/32-7"	5/32" x 3/32-7"	11/64" x 3/32-7"	3/16" x 3/32-7"	3/16" x 1/8-20"
	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)	Rad. Flow (ft.) (gpm)
25	42 4.20	44 4.80	45 5.60	45 6.40	46 7.40
30	43 4.60	45 5.30	46 6.10	47 7.00	47 8.10
35	44 4.90	46 5.70	47 6.60	49 7.50	49 8.70
40	45 5.20	47 6.10	48 7.00	50 8.10	50 9.30
45	46 5.60	48 6.50	49 7.40	52 8.50	52 9.90
50	46 5.90	49 6.80	50 7.90	53 9.00	53 10.40
55	47 6.10	50 7.10	51 8.20	54 9.40	54 10.90
60	47 6.40	50 7.40	51 8.60	54 9.90	54 11.40
65	48 6.70	51 7.80	52 8.90	55 10.20	55 11.80
70	48 6.90	51 8.10	53 9.30	55 10.70	55 12.30
75	49 7.20	52 8.30	54 9.60	56 11.00	56 12.70
80	50 7.50	52 8.70	55 10.00	56 11.50	56 13.10

* Nozzles must be purchased separately. See chart below.

Item Numbers and Ordering Information

Sprinkler Only		
Sprinkler Without Nozzle, Without Plug	30H	A08401
Sprinkler without Nozzle, With Plug	30WH	A08411

Nozzle Only			XX = Nozzle Size						
			U.S. Standard		3/32"	7/64"	1/8"	9/64"	5/32"
			Metric						
			2.38mm	2.78mm	3.18mm	3.57mm	3.97mm	4.37mm	4.76mm
Brass Straight Bore Nozzle	SBN-3	105842-XX	–	–	–	09	10	11	12
Brass Straight Bore Nozzle with Vane	SBN-3V	106131-XX	–	–	–	09	10	11	12
Brass 7° Low Angle Spreader	LAN-1-7	100225-XX	06	07	08	09	10	–	–
Brass 20° Low Angle Spreader	LAN-1-20	100226-XX	06	07	08	09	10	–	–
Brass Plug		100255							

Bold nozzle size number denotes the most common nozzle choice.

30H / 30WH

30H Brass Straight Bore Nozzle (SBN-3) with Plug *										METRIC		
bar @ Nozzle	NOZZLE SIZE (Stream Height: 1.1m)											
	3.57 MM (9/64")			3.97 MM (5/32")			4.37 MM (11/64")			4.76 MM (3/16")		
	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)
1.7	12.2	0.18	0.66	12.5	0.22	0.79	12.6	0.27	0.98	13.0	0.32	1.16
2.0	12.3	0.19	0.69	12.9	0.24	0.87	13.3	0.29	1.05	13.7	0.35	1.25
2.5	12.5	0.22	0.78	13.3	0.27	0.97	13.8	0.33	1.18	14.4	0.38	1.39
3.0	12.8	0.24	0.85	13.5	0.29	1.05	14.1	0.35	1.27	14.8	0.42	1.52
3.5	13.0	0.26	0.93	13.7	0.32	1.14	14.5	0.39	1.39	15.3	0.46	1.65
4.0	13.2	0.27	0.98	14.0	0.34	1.22	14.7	0.41	1.47	15.5	0.49	1.77
4.5	13.4	0.29	1.05	14.2	0.37	1.32	14.9	0.44	1.57	15.7	0.52	1.87
5.0	13.6	0.31	1.11	14.4	0.38	1.36	15.2	0.46	1.66	15.9	0.55	1.96
5.5	13.9	0.32	1.16	14.6	0.40	1.43	15.4	0.49	1.75	16.2	0.57	2.07

30H Brass Straight Bore Nozzle (SBN-3) with Spreader (LAN-1*)													METRIC		
bar @ Nozzle	NOZZLE SIZE (Stream Height: 1.1m)														
	3.57 mm x 2.38 mm (9/64" x 3/32") 7°			3.97 mm x 2.38 mm (5/32" x 3/32") 7°			4.37 mm x 2.38 mm (11/64" x 3/32") 7°			4.76 mm x 2.38 mm (3/16" x 3/32") 7°			4.76 mm x 3.18 mm (3/16" x 1/8") 20°		
	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)
1.7	12.2	0.26	0.95	12.5	0.30	1.09	12.6	0.35	1.27	13.0	0.40	1.45	13.0	0.47	1.68
2.0	12.3	0.29	1.03	12.9	0.33	1.18	13.3	0.38	1.36	13.7	0.43	1.56	13.7	0.50	1.81
2.5	12.5	0.31	1.13	13.3	0.37	1.32	13.8	0.42	1.52	14.4	0.48	1.74	14.4	0.56	2.01
3.0	12.8	0.35	1.24	13.5	0.40	1.45	14.1	0.46	1.65	14.8	0.53	1.90	14.8	0.61	2.21
3.5	13.0	0.37	1.35	13.7	0.43	1.55	14.5	0.50	1.80	15.3	0.57	2.06	15.3	0.66	2.38
4.0	13.2	0.40	1.43	14.0	0.46	1.65	14.7	0.53	1.92	15.5	0.61	2.20	15.5	0.71	2.54
4.5	13.4	0.42	1.52	14.2	0.49	1.77	14.9	0.56	2.03	15.7	0.64	2.32	15.7	0.75	2.69
5.0	13.6	0.44	1.60	14.4	0.52	1.86	15.2	0.60	2.15	15.9	0.68	2.46	15.9	0.79	2.84
5.5	13.9	0.47	1.70	14.6	0.55	1.98	15.4	0.63	2.27	16.2	0.73	2.61	16.2	0.83	2.98

30H Brass Straight Bore Nozzle (SBN-3) with Plug *										METRIC		
bar @ Nozzle	NOZZLE SIZE (Stream Height: 3m)											
	3.57 MM (9/64")			3.97 MM (5/32")			4.37 MM (11/64")			4.76 MM (3/16")		
	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)
1.7	13.0	0.18	0.66	13.4	0.22	0.79	13.7	0.27	0.98	14.0	0.32	1.16
2.0	13.2	0.19	0.69	13.7	0.24	0.87	14.0	0.29	1.05	14.4	0.35	1.25
2.5	13.6	0.22	0.78	14.1	0.27	0.97	14.4	0.33	1.18	15.0	0.38	1.39
3.0	14.0	0.24	0.85	14.5	0.29	1.05	14.8	0.35	1.27	15.7	0.42	1.52
3.5	14.2	0.26	0.93	15.0	0.32	1.14	15.3	0.39	1.39	16.2	0.46	1.65
4.0	14.4	0.27	0.98	15.3	0.34	1.22	15.6	0.41	1.47	16.5	0.49	1.77
4.5	14.6	0.29	1.05	15.6	0.37	1.32	15.9	0.44	1.57	16.8	0.52	1.87
5.0	14.9	0.31	1.11	15.8	0.38	1.36	16.3	0.46	1.66	17.0	0.55	1.96
5.5	15.2	0.32	1.16	16.0	0.40	1.43	16.8	0.49	1.75	17.2	0.57	2.07

30H Brass Straight Bore Nozzle (SBN-3) with Spreader (LAN-1*)													METRIC		
bar @ Nozzle	NOZZLE SIZE (Stream Height: 3m)														
	3.57 mm x 2.38 mm (9/64" x 3/32") 7°			3.97 mm x 2.38 mm (5/32" x 3/32") 7°			4.37 mm x 2.38 mm (11/64" x 3/32") 7°			4.76 mm x 2.38 mm (3/16" x 3/32") 7°			4.76 mm x 3.18 mm (3/16" x 1/8") 20°		
	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)	Rad. (m)	Flow (l/s)	Flow (m ³ /h)
1.7	13.0	0.26	0.95	13.4	0.30	1.09	13.9	0.35	1.27	13.9	0.40	1.45	13.9	0.47	1.68
2.0	13.2	0.29	1.03	13.7	0.33	1.18	14.0	0.38	1.36	14.4	0.43	1.56	14.4	0.50	1.81
2.5	13.6	0.31	1.13	14.1	0.37	1.32	14.4	0.42	1.52	15.0	0.48	1.74	15.0	0.56	2.01
3.0	14.0	0.35	1.24	14.5	0.40	1.45	14.8	0.46	1.65	15.7	0.53	1.90	15.7	0.61	2.21
3.5	14.2	0.37	1.35	15.0	0.43	1.55	15.3	0.50	1.80	16.2	0.57	2.06	16.2	0.66	2.38
4.0	14.4	0.40	1.43	15.3	0.46	1.65	15.6	0.53	1.92	16.5	0.61	2.20	16.5	0.71	2.54
4.5	14.6	0.42	1.52	15.6	0.49	1.77	15.9	0.56	2.03	16.8	0.64	2.32	16.8	0.75	2.69
5.0	14.9	0.44	1.60	15.8	0.52	1.86	16.3	0.60	2.15	17.0	0.68	2.46	17.0	0.79	2.84
5.5	15.2	0.47	1.70	16.0	0.55	1.98	16.8	0.63	2.27	17.2	0.73	2.61	17.2	0.83	2.98

* Nozzles must be purchased separately. See chart on previous page.

