



AQUOR® UNIVERSAL OUTLET

Flush-mounted stainless steel hydrant with hose connector.

A reliable, leak-proof water outlet that can be used anywhere water access is needed, on land or sea.

Ideal for marine vessels, campers, RVs, overland vehicles, storage tanks, DIY applications, and much more. Can be mounted horizontally or vertically.

- Water flow starts instantly when hose connector is inserted.
- High-performance Viton® O-rings ensure a reliable leak-proof seal, even in harsh conditions.
- Stainless steel body and pressure-closed valve provide zero-maintenance reliability for years.
- 316L alloy is marine-grade and highly resistant to corrosion.
- Crush-proof acetal resin hose connector rated for 150,000 cycles and 200 lbs of lateral force. Attach to any garden hose.
- Durable thermoplastic debris cover swivels to cover outlet.
- Hydrant can be mounted vertically or horizontally.
- Hydrant comes standard with 1/2" female NPT inlet. Optional 90° elbow and dual inlet also available.
- Each hydrant kit comes furnished with one hose connector and stainless steel mounting screws.
- Any 3/4" accessory (eg. timers, splitters, ball valves) can be attached to end of hose connector.
- Hose connector contains check valve for backflow protection. If needed, an inline vacuum breaker can be added.
- To configure outlet as an intake, remove the check valve.
- Hydrant will provide freeze protection in mild climates, but should be disconnected when not in use.

TECHNICAL INFO

- Inlet: 1/2" NPT
- Outlet: 3/4" Garden Hose Thread
- Flow rate: 6.8 GPM @ 52 PSI
- Operating water pressure: 25 - 125 PSI
- Operating temperature range: 0° - 140° F
- Warranty: 10-year stainless components, 5-year polymer

